



Rondo Lux

TYPE	HEIGHT in mm.	LENGTH in mm.	OUTPUT 55/45/20°C	OUTPUT 75/65/20°C
RL80.45	770	457	179 W.	335 W.
RL80.50	770	507	197 W.	370 W.
RL80.55	770	557	227 W.	425 W.
RL80.60	770	607	239 W.	449 W.
RL80.75	770	757	292 W.	548 W.
RL80.100	770	1007	393 W.	738 W.
RL120.45	1210	457	289 W.	543 W.
RL120.50	1210	507	319 W.	599 W.
RL120.55	1210	557	362 W.	680 W.
RL120.60	1210	607	383 W.	719 W.
RL120.75	1210	757	472 W.	886 W.
RL150.50	1490	507	385 W.	723 W.
RL150.60	1490	607	462 W.	866 W.
RL150.75	1490	757	568 W.	1066 W.
RL180.45	1810	457	446 W.	837 W.
RL180.50	1810	507	472 W.	885 W.
RL180.55	1810	557	531 W.	997 W.
RL180.60	1810	607	562 W.	1054 W.
RL180.75	1810	757	700 W.	1313 W.



Rondo Lux




TYPE	HEIGHT in mm.	LENGTH in mm.	ELECTRIC ELEMENT
RL80.45E	770	457	250 W.
RL80.50E	770	507	250 W.
RL80.60E	770	607	400 W.
RL80.100E	770	1007	600 W.
RL120.45E	1210	457	400 W.
RL120.50E	1210	507	600 W.
RL120.60E	1210	607	600 W.
RL120.75E	1210	757	800 W.
RL150.50E	1490	507	600 W.
RL150.60E	1490	607	800 W.
RL150.75E	1490	757	1000 W.
RL180.45E	1810	457	800 W.
RL180.50E	1810	507	800 W.
RL180.60E	1810	607	1000 W.
RL180.75E	1810	757	1250 W.



EL.AFSTAND.02
EL.BEDIENING.11
EL.BEDIENING.12
EL.BEDIENING.13

This radiator comes standard with the white EL.BEDIENING.08 thermostat. As an option, you can choose from the following:
Digital remote control
Round thermostat, white
Round thermostat, matte black
Round thermostat, chrome



Standard connection:

IMPORTANT!
For top connection, a flow tube is necessary.

Maximum operating pressure: 10 bar
Exponent n: 1,21

