



Mita

Mita



TYPE	HEIGHT in mm.	LENGTH in mm.	OUTPUT 55/45/20°C	OUTPUT 75/65/20°C
MT100.50	986	500	235 W.	438 W.
MT100.60	986	600	276 W.	513 W.
MT120.50	1259	500	292 W.	545 W.
MT120.60	1259	600	342 W.	638 W.
MT120.75	1259	750	417 W.	774 W.
MT150.50	1533	500	346 W.	649 W.
MT150.60	1533	600	406 W.	760 W.
MT150.75	1533	750	493 W.	921 W.
MT180.50	1806	500	398 W.	750 W.
MT180.60	1806	600	467 W.	878 W.
MT180.75	1806	750	568 W.	1065 W.




TYPE	HEIGHT in mm.	LENGTH in mm.	ELECTRIC ELEMENT
MT120.50E	1259	500	600 W.
MT120.60E	1259	600	600 W.
MT150.50E	1533	500	600 W.
MT150.60E	1533	600	800 W.
MT180.50E	1806	500	800 W.
MT180.60E	1806	600	800 W.




EL.AFSTAND.02
EL.BEDIENING.11
EL.BEDIENING.12
EL.BEDIENING.13

This radiator comes standard with the white EL.BEDIENING.08 thermostat. As an option, you can choose from the following:
Digital remote control
Round thermostat, white
Round thermostat, matte black
Round thermostat, chrome



Standard connection:



Maximum operating
pressure: 4 bar
Exponent n: 1,21

